

SUBMERSIBLE SEWAGE PUMPS **DPS SERIES**

OPERATING LIMITS

Fluid temperature up to + 40°C
Maximum operating depth 5m
Trans medium's PH:4~10

220V/50Hz.60Hz 110V/50Hz.60Hz
220V.110V/50Hz.60Hz are available on request.

Before order,you could choose "V/Hz" or other special requirement.



TECHNICAL DATA

Type	Power HP kW	Rpm	MAX.Flow (mm)	Max.Head (m)	Pump Dia (mm)
DPS4-10-0.55	0.75 0.55	2850	4	10	38
DPS6-12.5-0.75	1 0.75	2850	6	12.5	51
DPS4-10.0.55	0.75 0.55	2850	4	10	38
DPS7-10-0.75	1 0.75	2850	7	10	51
DPS15-7-1.2	1.5 1.2	2850	15	7	51
DPS9-22-2.2	2.5 2.2	2850	9	22	51
DPS15-15-2.2	2.5 2.2	2850	15	15	51
DPS35-7-2.2	2.5 2.2	2850	35	7	76
DPS25-10-2.2	2.5 2.2	2850	25	10	64
DPS50-7-3	4 3	2850	50	7	102
DPS15-30-3	4 3	2850	15	30	64
DPS35-15-3	4 3	2850	35	15	76
DPS25-15-3	4 3	2850	25	15	64