



ESE2000S
ESE3500S
ESE5000S



ESE2000A(L)
ESE3500A(L)
ESE5000A(L) ESE3700

TECHNICAL DATA

Model	ESE2000S	ESE3500S	ESE5000S	ESE2000A(L)	ESE3500A(L)	ESE5000A(L)	ESE2000AE	ESE3500AE	ESE5000AE
Frequency (HZ)	50								
Rated Voltage (V)	220								
Max. AC Output (kW)	2.0	3	5	2.0	3	5	2.0	3	5
Rated AC Output (kW)	1.8	2.8	4.8	1.8	2.8	4.8	1.8	2.8	4.8
DC. Output (V-A)	12V/3.8A								
Power factor (V)	1.0								
Phase	Single-phase								
Excitation System	Transistorized self-excitation constant voltage (AVR)								
Model	170F	178F	186F	170F	178F	186F	170FE	178FE	186FE
Type	Single-cylinder:vertical, 4-stroke, air-cooled, direct-injection								
Starting system	Recoil						Electric		
Displacement(cc)	211	296	406	211	296	406	211	296	406
Rated Output (PS/rpm)	3.8/3600	5.5/3600	8.5/3600	3.8/3600	5.5/3600	8.5/3600	3.8/3600	5.5/3600	8.5/3600
Fuel Tank Capacity (L)	2.5	3.5	5.5	15	15	15	15	15	15
Lube. Oil Capacity (L)	0.75	1.1	1.65	0.75	1.1	1.65	0.75	1.1	1.65
Dimension (LXWXH)mm	595X425X535	630X480X575	710X500X615	645X480X560	715X480X580	715X480X645	645X480X560	715X480X580	715X480X645
G.W (kg)	53	65	95	53	65	95	53	65	95
20'FCL(pcs)	204	180	135	156	140	108	156	140	108

DIESEL GENERATOR SETS

Brush alternator running more steadily
AVR and carbon brush voltage adjuster make output voltage steady-going
Non-fuse circuit breaker perform an overload protection function.
12V8.3A DC can be used in various of vehicle, ship battery charging up.
Big fuel tank offer long time running without adding fuel.
With auto protective device of low fuel pressure.
Offer electrical startup diesel generator on request