

STAINLESS STEEL

ANTICORROSION SUBMERSIBLE PUMP

MODEL

200QJSF

TECHNICAL DATA

MODEL	Power		Voltage V	Ampere A	Capacity (m ³ /h)	Head (m)	Efficiency (%)	Pipe Dia (G)	Pump casing external diameter (mm)
	kW	HP							
200QJSF63-36/3	11	15	380	28	63	36	74		184
200QJSF63-48/4	15	20	380	35	63	48	74		184
200QJSF63-60/5	18.5	25	380	42	63	60	74		184
200QJSF63-72/6	22	30	380	48	63	72	74		184
200QJSF63-84/7	25	34	380	54	63	84	74		184
200QJSF63-96/8	30	40	380	62	63	96	74		184
200QJSF63-120/10	37	50	380	70	63	120	74		184
200QJSF63-144/12	45	60	380	80	63	144	74		184
200QJSF63-180/15	55	75	380	92	63	180	74		184
200QJSF63-204/17	63	85	380	103	63	204	74		184
200QJSF63-240/20	75	100	380	115	63	240	74		184
200QJSF63-288/24	90	120	380	135	63	288	74		184
200QJSF80-33/3	11	15	380	28	80	33	75		184
200QJSF80-44/4	15	20	380	35	80	44	75		184
200QJSF80-55/5	18.5	25	380	42	80	55	75		184
200QJSF80-66/6	22	30	380	48	80	66	75		184
200QJSF80-77/7	25	34	380	54	80	77	75	4"/5"	184
200QJSF80-88/8	30	40	380	62	80	88	75		184
200QJSF80-110/10	37	50	380	70	80	110	75		184
200QJSF80-132/12	45	60	380	80	80	132	75		184
200QJSF80-165/15	55	75	380	92	80	165	75		184
200QJSF80-187/17	63	80	380	103	80	187	75		184
200QJSF80-220/20	75	100	380	115	80	220	75		184
200QJSF80-264/24	90	120	380	135	80	264	75		184
200QJSF100-45/3	18.5	25	380	42	100	45	76		184
200QJSF100-60/4	25	30	380	48	100	60	76		184
200QJSF100-75/5	30	40	380	54	100	75	76		184
200QJSF100-90/6	37	50	380	62	100	90	76		184
200QJSF100-105/7	45	60	380	70	100	105	76		184
200QJSF100-120/8	55	75	380	80	100	120	76		184
200QJSF100-135/9	63	85	380	90	100	135	76		184
200QJSF100-165/11	75	100	380	103	100	165	76		184
200QJSF100-195/13	90	120	380	115	100	195	76		184



Precision casting stainless steel
(Connect piece, pump body and impeller)